



FRONT ELEVATION

5 4				$\oplus \ominus$	THIRD ANGLE PROJECTION U.N.O.	
3				mm	ALL DIMENSIONS IN MILLIMETRES U.N.O. DO NOT SCALE FROM DRAWINGS	
2				mm	IF IN DOUBT, ASK	
1				© LANDMARK PRODUCTS LIMITED		
	REVISION	DRAWN	DATE	THIS DOCUMENT REMAINS THE PROPERTY OF LANDMARK PRODUCTS LIMITED. UNAUTHORISED USE OF THIS DOCUMENT IN ANY FORM IS PROHIBITED.		











END ELEVATION

SCALE (1:50)

Queensland 4508

Landmark Products Limited. A.B.N. 99 112 000 843 55-57 Kabi Circuit, Deception Bay P.O. Box 603, Deception Bay www.landmarkpro.com.au

PH: 1300 768 230 FAX: 1300 768 260

landmark@landmarkpro.com.au

AWN	CLIENT NAME							
MAF ECKED	LANDMARK PRODUCTS LIMITED							
-	PROJECT							
TE -	STANDARD K690 "BRIGHTON" SHELTER RANGE K692 BRIGHTON,AP, IG, S/S FIXINGS							
ALE	1002 Bittofff Ott,Air , 10, 0/0 i bitto							
OTED	DRAWING TITLE	DRAWING NUMBER	SHEET	REVISI				
GE A 2	PRELIM - PLAN & ELEVATIONS	K6924A*A*IM*	001	0				

001

GENERAL NOTES:

- 1. DURING CONSTRUCTION THE STRUCTURE SHALL BE MAINTAINED IN A STABLE CONDITION AND NO PART SHALL BE OVER STRESSED.
- 2. PRIOR TO COMMENCEMENT OF WORKS THE BUILDER SHALL SATISFY THEMSELVES OF THE CORRECT LOCATIONS OF ALL EXISTING SERVICES WHETHER INDICATED OR NOT ON THE PLANS.
- 3. LOCATING OF THE STRUCTURE, INCLUDING CO-ORDINATES IF APPLICABLE, IS THE RESPONSIBILITY OF THE CLIENT AND/OR THE CLIENT'S SITE REPRESENTATIVE.
- 4. STRUCTURE HAS BEEN DESIGNED AS A CLASS 10A STRUCTURE AND IN ACCORDANCE TO THE FOLLOWING AUSTRALIAN STANDARDS:
 - AS1170.1, AS1170.2, AS1720.1, AS3600 AND AS4100, AS1664.
- 5. STRUCTURE IS SUITABLE FOR N3 AREAS AND HAS BEEN DESIGNED WITH AN ANNUAL RECURRANCE INTERVAL OF 100 YEARS.
- 6. SITE COVERAGE IS 15 m2 (ROOF AREA).
- 7. THE FOOTING HAS BEEN DESIGNED ASSUMING:
 - SITE CLASS S OR M OR H
 - ALLOWABLE SOIL BEARING CAPACITY OF 100kPa
 - SOIL ADHESION OF 10kPa
- (TO BE VERIFIED ON SITE).
- 8. FOR SLABS ON GROUND, ALL TOPSOIL AND UPPER STRATA CONTAINING SOFT OR ORGANIC MATTER ARE TO BE REMOVED AND REPLACED WITH SELECT COMPACTED FILL.
- 9. ALL FILL TO BE CLEAN, PLACED IN LAYERS NOT EXCEEDING 200mm AND COMPACTED TO 95% STANDARD COMPACTION.
- 10. EARTHWORKS SHALL BE CARRIED OUT IN ACCORDANCE WITH CRITERIA AND PROCEDURES SET OUT IN AS3798 GUIDELINES ON EARTHWORKS FOR COMMERCIAL AND RESIDENTIAL DEVELOPMENTS.

PRELIMINARY DRAWING ONLY - NOT FOR CONSTRUCTION